



SYMBOL: **4933464967** MANUFACTURER: **Milwaukee** EAN: **4058546229122**



M12 ONEFTR38-201C - 3/8" Digital torque wrench +/- 2%, 12 V, 2.0 Ah, FUEL™, ONE-KEY™, in case, with battery and charger

- Voltage: 12 V
- Accuracy: CW ±2%, CCW ±3%
- Torque range: 13.6 - 135.6 Nm
- No load speed: 0-100 rpm
- Tool holder: 3/8" square
- Battery type: Li-ion
- No. of batteries supplied: 1
- Battery pack capacity: 2.0 Ah
- Charger supplied: 40 min
- Length: 591.8 mm
- Weight with battery pack: 2.5 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



4 439,00 zł **-10%**

3 995,10 zł (tax excl.)

(4 913,97 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://dokrecanie-kontrolowane.pl/en/20571-m12-oneftr38-201c-38-digital-torque-wrench-2-12-v-20-...>

DESCRIPTION

- Milwaukee Tool's first digital torque wrench, delivers up to 50% faster installation by replacing the hand tool.
- Provides 13.6 - 135.6 Nm of torque range and accuracy within ±2% for torque critical fasteners.
- Faster, more productive torque reporting with ONE-KEY™ providing torque data and customisable reports for inspectors or owners.
- Adjustable run-down torque to control the tools output torque via the motor to prevent over torque.
- Four measurement modes (ft-lb, in-lb, Nm, Kg-cm).
- Durable design to withstand the most demanding jobsite environments.
- Four notification modes that the tool is reaching, meeting or exceeding the torque target (audible, LED, LCD, and vibratory).
- Six pre-programmed languages including English, Spanish and French.
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™-ION battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#).
- Supplied in case (Kitbox) with battery and charger.

FEATURES

| | |
|--------------------------|------------------|
| Symbol | M12ONEFTR38-201C |
| L [mm] | 591.80 |
| Waga [kg] | 2.50 |
| Typ | ONE-KEY |
| Nm min | 13.60 |
| Nm max | 135.60 |
| Dokładność | ±2% |
| Ilość akumulatorów | 1 |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 12 |