


R - Nasadki 1/4" 6-kątnie calowe




ASME B107.1

- Profil OGV®: większa siła i bezpieczeństwo, ochrona nakrętek.
- Wykończenie: chromowane błyszczące.
- Dostępne w zestawie na stojaku metalowym (symbol R.40U).

➤	A ["]	⊘ [mm]	d [mm]	d1 [mm]	L [mm]	L1 [mm]	ΔΔ [g]
R.3/16	3/16	6	11,2	8,0	22	4,75	8,20
R.7/32	7/32	6	11,2	9,0	22	5,50	8,30
R.1/4	1/4	6	11,2	10,1	22	6,00	9,30
R.9/32	9/32	6	11,0	11,0	22	6,00	8,90
R.5/16	5/16	6	12,0	12,0	22	6,50	11,50
R.11/32	11/32	6	13,2	13,2	22	6,50	14,50
R.3/8	3/8	6	14,7	14,7	22	7,80	17,80
R.13/32	13/32	6	14,7	14,7	22	7,80	17,00
R.7/16	7/16	6	15,8	15,8	22	9,00	19,50
R.1/2	1/2	6	17,7	17,7	22	10,00	24,50
R.9/16	9/16	6	18,7	18,7	22	10,00	25,20

R.E - Nasadki 1/4" 12-kątnie metryczne




NF ISO 2725-1, NF ISO 1711-1, ISO 2725-1, ISO 1711-1, DIN 3124, ASME B107.5

- Profil OGV®: większa siła i bezpieczeństwo, ochrona nakrętek.
- Wykończenie: chromowane błyszczące.

➤	A [mm]	⊘ [mm]	d [mm]	d1 [mm]	L [mm]	L1 [mm]	ΔΔ [g]
R.5,5E	5,5	12	11,2	8,8	22	4,80	8,40
R.6E	6,0	12	11,2	9,4	22	5,60	8,60
R.7E	7,0	12	11,0	11,0	22	6,00	9,20
R.8E	8,0	12	12,0	12,0	22	6,50	11,50
R.9E	9,0	12	13,2	13,2	22	6,50	14,30
R.10E	10,0	12	14,7	14,7	22	7,80	17,70
R.11E	11,0	12	15,8	15,8	22	9,00	19,40
R.12E	12,0	12	17,0	17,0	22	9,50	23,20
R.13E	13,0	12	17,7	17,7	22	10,00	23,70
R.14E	14,0	12	18,7	18,7	22	10,00	26,10

R.E - Nasadki 1/4" 12-kątnie calowe



ASME B107.1

- Profil OGV®: większa siła i bezpieczeństwo, ochrona nakrętek.
- Wykończenie: chromowane błyszczące.

➤	A ["]	⊘ [mm]	d [mm]	d1 [mm]	L [mm]	L1 [mm]	ΔΔ [g]
R.3/16E	3/16	12	11,2	8,0	22	4,75	8,20
R.7/32E	7/32	12	11,2	9,0	22	5,50	8,30
R.1/4E	1/4	12	11,2	10,1	22	6,00	9,30
R.9/32E	9/32	12	11,2	10,6	22	6,00	8,90
R.5/16E	5/16	12	12,0	12,0	22	6,50	11,50
R.11/32E	11/32	12	13,0	13,0	22	6,50	14,50
R.3/8E	3/8	12	14,7	14,7	22	7,80	17,80
R.13/32E	13/32	12	14,7	14,7	22	7,80	17,00
R.7/16E	7/16	12	15,8	15,8	22	9,00	19,5
R.1/2E	1/2	12	17,7	17,7	22	10,00	24,5
R.9/16E	9/16	12	18,7	18,7	22	10,00	25,20

