


**K.B - Nasadki 3/4" 12-kątne calowe**




**ASME B107.1**

- Profil OGV®: większa siła i bezpieczeństwo, ochrona nakrętek.
- Umożliwiają blokowanie akcesoriów wyposażonych w zatraski.
- Wyposażone w przycisk szybkiego odblokowywania.
- Wykończenie: chromowane satynowane.

➤	A ["]	⊘ [mm]	d [mm]	d1 [mm]	L [mm]	L1 [mm]	ΔΔ [g]
<b>K.3/4B</b>	3/4	12	36	30,1	51,0	14	207
<b>K.7/8B</b>	3/4	12	36	33,6	51,0	14	220
<b>K.15/16B</b>	15/16	12	36	35,7	52,5	14	233
<b>K.1"B</b>	1"	12	36	38,0	52,5	14	250
<b>K.1"1/16B</b>	1 1/16"	12	36	39,7	52,5	18	232
<b>K.1"1/8B</b>	1 1/8"	12	36	41,6	52,5	18	241
<b>K.1"3/16B</b>	1 3/16"	12	36	43,2	59,0	20	280
<b>K.1"1/4B</b>	1 1/4"	12	36	45,9	59,0	22	304
<b>K.1"5/16B</b>	1 5/16"	12	36	48,1	59,0	22	326
<b>K.1"3/8B</b>	1 3/8"	12	36	50,1	59,0	24	343
<b>K.1"7/16B</b>	1 7/16"	12	36	51,0	59,0	24	339
<b>K.1"1/2B</b>	1 1/2"	12	40	54,3	66,9	27	478

➤	A ["]	⊘ [mm]	d [mm]	d1 [mm]	L [mm]	L1 [mm]	ΔΔ [g]
<b>K.1"9/16B</b>	1 9/16"	12	40	56,0	66,9	27	498
<b>K.1"5/8B</b>	1 5/8"	12	40	57,3	66,9	27	498
<b>K.1"11/16B</b>	1 11/16"	12	40	60,7	66,9	27	564
<b>K.1"3/4B</b>	1 3/4"	12	40	62,2	66,9	28	586
<b>K.1"13/16B</b>	1 13/16"	12	40	63,5	75,0	30	641
<b>K.1"7/8B</b>	1 7/8"	12	40	66,2	75,0	33	699
<b>K.2"B</b>	2"	12	40	68,5	75,0	33	698
<b>K.2"1/8B</b>	2 1/8"	12	45	74,0	75,0	36	880
<b>K.2"3/16B</b>	2 3/16"	12	45	74,7	75,0	36	855
<b>K.2"1/4B</b>	2 1/4"	12	45	77,1	75,0	36	913

**K.LA - Nasadki 3/4" długie 6-kątne metryczne**




**NF ISO 2725-1, NF ISO 1711-1, ISO 2725-1, ISO 1711-1, DIN 3124, ASME B107.5**

- Profil OGV®: większa siła i bezpieczeństwo, ochrona nakrętek.
- Umożliwiają blokowanie akcesoriów wyposażonych w zatraski.
- Wyposażone w przycisk szybkiego odblokowywania.
- Wykończenie: chromowane satynowane.

➤	A [mm]	⊘ [mm]	d [mm]	d1 [mm]	L [mm]	L1 [mm]	ΔΔ [g]
<b>K.19LA</b>	19	6	36	30,1	90	18	339
<b>K.21LA</b>	21	6	36	32,0	90	18	367
<b>K.22LA</b>	22	6	36	33,4	90	21	391
<b>K.23LA</b>	23	6	38	36,0	90	21	461
<b>K.24LA</b>	24	6	38	36,0	90	24	400
<b>K.26LA</b>	26	6	36	38,9	90	24	474
<b>K.27LA</b>	27	6	38	39,7	90	27	480
<b>K.29LA</b>	29	6	40	42,0	90	27	505
<b>K.30LA</b>	30	6	40	43,2	90	30	530

➤	A [mm]	⊘ [mm]	d [mm]	d1 [mm]	L [mm]	L1 [mm]	ΔΔ [g]
<b>K.32LA</b>	32	6	40	45,9	90	33	540
<b>K.33LA</b>	33	6	45	48,1	90	33	600
<b>K.34LA</b>	34	6	45	48,4	90	33	656
<b>K.35LA</b>	35	6	45	50,1	90	33	707
<b>K.36LA</b>	36	6	45	51,0	90	36	672
<b>K.38LA</b>	38	6	45	54,3	90	36	772
<b>K.41LA</b>	41	6	45	57,3	90	40	778
<b>K.42LA</b>	42	6	45	59,5	90	40	863

**KT.A - Nasadki trzpieniowe 3/4" do śrub 6-kątnych metrycznych**



- Końcówki wymienne blokowane trzpieniem
- Wykończenie: chromowane z końcówką fosforanowaną.

➤	A [mm]	d [mm]	Końcówki	L [mm]	L1 [mm]	ΔΔ [g]
<b>KT.14A</b>	14	36	ET.1914	74,5	25	297
<b>KT.17A</b>	17	36	ET.1917	74,5	25	307
<b>KT.19A</b>	19	36	ET.1919	74,5	25	314
<b>KT.22A</b>	22	36	ET.1919	74,5	25	314

