


Łączniki - złącze 20 x 7 mm



- Umożliwiają zastosowanie:
  - końcówek 9 x 12 dla kluczy o maksymalnym zakresie do 100 Nm.
  - końcówek 14 x 12 dla kluczy o maksymalnym zakresie do 600 Nm.

№	Zaczepek	ΔΔ [g]
<b>J.274</b>	9 x 12	135
<b>S.284</b>	14 x 18	145

Końcówki widelkowe – złącze 20 x 7 mm



- Używane z kluczami dynamometrycznymi serii 203, 306R i 446.

№	A [mm]	B [mm]	E [mm]	L [mm]	ΔΔ [g]
<b>20.10</b>	10	24	6,0	105	60
<b>20.11</b>	11	24	6,0	105	60
<b>20.12</b>	12	29	6,0	106	60
<b>20.13</b>	13	29	6,0	106	60
<b>20.14</b>	14	29	6,0	106	65
<b>20.15</b>	15	40	7,5	109	105
<b>20.16</b>	16	40	7,5	109	105
<b>20.17</b>	17	40	7,5	109	105
<b>20.18</b>	18	40	7,5	109	100
<b>20.19</b>	19	40	7,5	109	100
<b>20.21</b>	21	53	8,0	112	145
<b>20.22</b>	22	53	8,0	112	145
<b>20.23</b>	23	53	8,0	112	145
<b>20.24</b>	24	53	8,0	112	140
<b>20.26</b>	26	53	8,0	112	130
<b>20.27</b>	27	66	9,0	115	185
<b>20.28</b>	28	66	9,0	115	185
<b>20.29</b>	29	66	9,0	115	185
<b>20.30</b>	30	66	9,0	115	185
<b>20.32</b>	32	66	9,0	115	180
<b>20.35</b>	35	74	10,0	118	220
<b>20.36</b>	36	74	10,0	118	220


Akcesoria specjalne

S.305P Rękojeść obrotowa



- Umożliwiają utrzymanie klucza w pozycji równoległej do płaszczyzny dokręcania.
- Używana z grzechotkami i zabierakami kwadratowymi 3/8" i 1/2".
- Wymiary śr. maks.: 45 mm.
- Długość: 66 mm.
- Masa: 110 g.

Końcówka Crowfoot 3/8" do rur, 12-kątna



- Wysoka główka 12-kątna cienkościenna.
- Dostosowana do specyfikacji lotniczych.
- Zabierak kwadratowy: 3/8".
- Wymiary: 5/8" --> 1 1/16.
- Wykończenie: chromowane.

№	A ["]	B [mm]	C [mm]	E [mm]	L [mm]	L1 [mm]	ΔΔ [g]
<b>4920FL</b>	5/8	18,3	24,2	24,2	19,05	11,20	40
<b>4922FL</b>	11/16	18,3	26,3	26,3	20,20	12,50	44
<b>4924FL</b>	3/4	18,3	29,2	29,2	21,40	14,00	53
<b>4926FL</b>	13/16	18,9	31,1	31,1	22,60	15,40	56
<b>4928FL</b>	7/8	19,3	33,8	33,8	25,00	16,70	67
<b>4930FL</b>	15/16	19,0	35,9	35,9	24,20	17,30	68
<b>4932FL</b>	1	19,8	37,7	37,7	26,20	19,00	77
<b>4934FL</b>	1-1/16	20,0	39,5	39,5	27,00	18,10	84

